

# Safe For Your Coils And For You

Some coil cleaners do more harm than good

## CC-140 – The Right Touch

Beware of “coil cleaners” that can actually damage coils and create noxious fumes. The award-winning CC-140 CoilPro® applies a thick layer of non-fuming CoilShine® expanding foam cleaner to loosen stuck-on deposits right before your eyes. With pressure regulation at your fingertips, you can quickly flush loosened deposits down the condensate drain without damaging the delicate fins or overwhelming the drain pan. And since dirty coils won't come to you, the CoilPro includes a built in ergonomic dolly with stair glides. For total mobility, just flip a switch and go from AC power to the on-board 12 V rechargeable battery. A control valve allows you to choose from a garden hose water supply or either of the two integrated tanks.



PATENT PENDING



### CC-140

CoilPro Battery Powered or 115 V Coil Cleaner, including 25' hose, spray gun with 18" wand, four nozzles (foaming, two flat spray and pinpoint), and a 1 gallon bottle of CoilShine

**Note:** Call for accessories.

### Wet/Dry Coil Cleaning System:

An unbeatable package of innovative technology, the CC-140-KIT combines the CC-140 with our CoilVac® for a complete coil cleaning system.

### CC-140-KIT

Same as CC-140 with a CoilVac Dry HEPA Vacuum, CoilVac mounting bracket and tool bin



## FEATURES

- > Deep cycle 12 V rechargeable battery or AC power input
- > Integrated 5 gallon water tank and 5 gallon chemical tank
- > Control valve to inject chemicals at 6:1 ratio (can be factory adjusted)
- > 18" wand and four custom nozzles
- > Heavy-duty ergonomic cart with stair glides
- > Wide variety of custom attachments



Specifications	CC-140
Motor Power	0.2 HP
Input Power	12 amps, 12 V, DC rechargeable VRLA battery or 3 amps, 115 V, 50/60 Hz AC Optional: 1.5 amps, 230 V, 50/60 Hz
Recharge Power	Standard: 1 amp, 115 V, 50/60 Hz AC Optional: 0.5 amps, 230 V, 50/60 Hz
Water Requirements	Maximum 120 PSI
Output Water Pressure	Variable, 40-140 PSI
Output Water Flow	Variable, 0.25-1 GPM
Pump	Positive displacement diaphragm
Water Tank	5 gallons
Soap Tank	5 gallons
Dimensions	44" high x 26" wide x 18" deep
Weight	75 lbs net dry

FOR MORE INFORMATION CONTACT

**Goodway Technologies Corporation**  
 420 West Avenue, Stamford, CT 06902-6384 U.S.A.  
 Tel: +1-203-359-4708 • Fax: +1-203-359-9601  
 E-Mail: [goodway@goodway.com](mailto:goodway@goodway.com)  
[www.goodway.com](http://www.goodway.com)